# MELT PENDANT LED



Melt is evocative of molten glass, the interior of a melting glacier or images of deep space. An imperfect, organic and naturalistic light that produces a mesmerizing hot-blown glass elect. Melt is created through a process of blow moulding and vacuum metallisation to achieve melted orbs with abundant and unusual luminosity that reœectsand enhances its environment.

2014 Year of Design **Product Weight** 2.44kg

**Finishing Process** Semi-Metallised, Plated

Surface Mount Shape/Diameter Dome, 11.5cm

**Power Method** Mains

H03VV-F 2 x 0,75 mm2 Cable Spec

Cable Type/Length Clear, 250cm 6W LED **Light Source** Max Wattage 9W 800 Lumens CRI >90 **Colour Temperature** 3000K

Dimmability Mains Dimmable, Leading & Trailing Edge

Voltage 220-240V **Environment** Indoor

LEDRING01Y, LEDDRIVER01EU **Spares** 

Certification/Electrical Class Certiÿed for NZ/AUS











### **SILVER**

Code MES03CH-PEUM2 **Shade Code** MES01CH **Shade Material Polycarbonate** Shade Colour/Finish Silver, Mirrored LEDP08CHEU Fitting Code **Fitting Material** Steel Fitting Colour/Finish Silver, Polished

Service Offer Quick Ship

#### **GOLD**

Code MES03GO-PEUM2 **Shade Code** MES01G **Shade Material Polycarbonate** Shade Colour/Finish Gold, Mirrored Fitting Code LEDP08GOEU Fitting Material Steel

Fitting Colour/Finish Gold, Polished

Service Offer Quick Ship



# MELT PENDANT LED



Melt is evocative of molten glass, the interior of a melting glacier or images of deep space. An imperfect, organic and naturalistic light that produces a mesmerizing hot-blown glass elect. Melt is created through a process of blow moulding and vacuum metallisation to achieve melted orbs with abundant and unusual luminosity that reœectsand enhances its environment.

2014 Year of Design **Product Weight** 2.44kg

**Finishing Process** Semi-Metallised, Plated

Surface Mount Shape/Diameter Dome, 11.5cm

**Power Method** Mains

H03VV-F 2 x 0,75 mm2 Cable Spec

Cable Type/Length Clear, 250cm 6W LED **Light Source** Max Wattage 9W 800 Lumens CRI >90 **Colour Temperature** 3000K

Dimmability Mains Dimmable, Leading & Trailing Edge

Voltage 220-240V **Environment** Indoor

LEDRING01Y, LEDDRIVER01EU **Spares** 

Certification/Electrical Class Certiÿed for NZ/AUS











### COPPER

Code MES03CO-PEUM2 **Shade Code** MES01CO **Shade Material Polycarbonate** Shade Colour/Finish Copper, Mirrored LEDP08COEU Fitting Code Fitting Material

Fitting Colour/Finish Copper, Polished

Service Offer Quick Ship

### **SMOKE**

Code MES03SM-PEUM2 **Shade Code** MES01SM **Shade Material Polycarbonate** Shade Colour/Finish Smoke, Mirrored Fitting Code LEDP08CHEU

**Fitting Material** Steel

Fitting Colour/Finish Silver, Polished

Service Offer Quick Ship

